

# N2MBC10

## Multi-Bay Battery Charger



N 2 G R O U P <sup>TM</sup>



N2MBC10-PANCF-30/50

### MODELS SUPPORTED

Panasonic CF-30/31 CF-52/53

### CAPACITY

Durable 10 Bay Configuration

### CHARGING

4 Hours - 1 to 10 Batteries

Charge Power 15W max

Discharge Power 3W max

### INTELLIGENT

Integrated smart technology optimizing battery life cycle management.

Friendly user interface with LCD and LED indicators alert user of charging status and when recalibration or battery replacement is necessary.

### RECALIBRATION

Feature helps to optimize battery life and ensures batteries are displaying accurate run time and charge percentage.

### ELECTRICAL

100V to 240V (50Hz - 60Hz) 4.5A

### TEMPERATURE

Operational:	32°F to 104°F	(0°C to 40°C)
Non-operational:	-4°F to 140°F	(-20°C to 60°C)

### DIMENSIONS

Depth:	11.5 in	(292.1 mm)
Width:	25 in	(635 mm)
Height:	8 in	(203.2 mm)
Weight:	16 lbs	(7257.5 g)

### CERTIFICATIONS

UL, FCC, CE & CSA



**Ridgeline** <sup>TM</sup>  
TECHNOLOGY

[www.Ridgeline-Tech.com](http://www.Ridgeline-Tech.com) 888.660.8688